

TYPE 4

Enviroline® Series Single-Door Enclosures

Application -

Designed to house electrical and electronic controls, instruments and components. Provides protection from dust, oil and water. For outdoor application a drip shield is recommended.

Construction -

- 0.075" carbon steel.
- Seams continuously welded and ground smooth.
- Flange trough collar around all sides of door opening.
- Oil-resisitant gasket.
- Collar studs provided for mounting optional panels.
- Concealed hinge.
- Removable and interchangeable doors.
- Black quarter turn latches.
- Latches are opened or closed with a screwdriver.
- Mounting holes in back of enclosure.
- Mounting hardware, sealing washer and hole plug included.
- Removable print pocket.
- Ground studs on door and body.

Options -

- Optional tamper-resistant inserts are available.
- Optional mounting feet available.
- Door hardware available.

Finish -

ANSI-61 gray powder coating inside and out. Optional panels are powder coated white.

Industry Standards -

NEMA Type 4, 12, & 13
UL Listed Type 4 & 12
CSA Type 4 & 12
IEC 60529 IP 66

Notes -

Interchangeable latches and handles available in the accessory section.

TYPE 4 ENVIROLINE® SERIES SINGLE-DOOR ENCLOSURES

ENCLOSURES						SUB-PANEL				
Catalog No.	Height (A)	Width (B)	Depth (C)	Product Code	List Price	Catalog No.	Panel Height (D)	Panel Width (E)	Product Code	List Price
SCE-12EL1206LP	12.00	12.00	6.00	E3	183.29	SCE-12DLP12	9.00	9.00	P3	13.67
SCE-12EL2406LP	12.00	24.00	6.00	E3	218.97	SCE-12P24	9.00	21.00	P3	27.86
SCE-16EL1206LP	16.00	12.00	6.00	E3	194.36	SCE-16P12	13.00	9.00	P3	14.81
SCE-16EL1208LP	16.00	12.00	8.00	E3	205.44	SCE-16P12	13.00	9.00	P3	14.81
SCE-16EL1408LP	16.00	14.00	8.00	E3	211.59	SCE-16DLP14	13.00	11.00	P3	17.72
SCE-16EL1606LP	16.00	16.00	6.00	E3	210.37	SCE-16P16	13.00	13.00	P3	24.57
SCE-16EL1608LP	16.00	16.00	8.00	E3	234.97	SCE-16P16	13.00	13.00	P3	24.57
SCE-16EL2006LP	16.00	20.00	6.00	E3	236.19	SCE-20P16	17.00	13.00	P3	30.37
SCE-16EL2008LP	16.00	20.00	8.00	E3	237.42	SCE-20P16	17.00	13.00	P3	30.37
SCE-20EL1206LP	20.00	12.00	6.00	E3	209.13	SCE-20P12	17.00	9.00	P3	23.14
SCE-20EL1606LP	20.00	16.00	6.00	E3	225.12	SCE-20P16	17.00	13.00	P3	30.37
SCE-20EL1608LP	20.00	16.00	8.00	E3	237.42	SCE-20P16	17.00	13.00	P3	30.37
SCE-20EL1612LP	20.00	16.00	12.00	E3	263.25	SCE-20P16	17.00	13.00	P3	30.37
SCE-20EL2006LP	20.00	20.00	6.00	E3	242.34	SCE-20P20	17.00	17.00	P3	35.44
SCE-20EL2008LP	20.00	20.00	8.00	E3	255.87	SCE-20P20	17.00	17.00	P3	35.44
SCE-20EL2012LP	20.00	20.00	12.00	E3	284.17	SCE-20P20	17.00	17.00	P3	35.44
SCE-20EL2408LP	20.00	24.00	8.00	E3	275.56	SCE-24P20	21.00	17.00	P3	45.57
SCE-24EL1206LP	24.00	12.00	6.00	E3	218.97	SCE-12P24	9.00	21.00	P3	27.86
SCE-24EL1606LP	24.00	16.00	6.00	E3	239.89	SCE-24P16	21.00	13.00	P3	32.92
SCE-24EL1608LP	24.00	16.00	8.00	E3	253.42	SCE-24P16	21.00	13.00	P3	32.92
SCE-24EL2006LP	24.00	20.00	6.00	E3	260.80	SCE-24P20	21.00	17.00	P3	45.57
SCE-24EL2008LP	24.00	20.00	8.00	E3	275.56	SCE-24P20	21.00	17.00	P3	45.57
SCE-24EL2010LP	24.00	20.00	10.00	E3	292.78	SCE-24P20	21.00	17.00	P3	45.57
SCE-24EL2012LP	24.00	20.00	12.00	E3	307.54	SCE-24P20	21.00	17.00	P3	45.57
SCE-24EL2016LP	24.00	20.00	16.00	E3	337.06	SCE-24P20	21.00	17.00	P3	45.57
SCE-24EL2406LP	24.00	24.00	6.00	E3	281.71	SCE-24P24	21.00	21.00	P3	53.18
SCE-24EL2408LP	24.00	24.00	8.00	E3	297.70	SCE-24P24	21.00	21.00	P3	53.18
SCE-24EL2410LP	24.00	24.00	10.00	E3	314.93	SCE-24P24	21.00	21.00	P3	53.18
SCE-24EL2412LP	24.00	24.00	12.00	E3	329.69	SCE-24P24	21.00	21.00	P3	53.18
SCE-24EL2416LP	24.00	24.00	16.00	E3	362.90	SCE-24P24	21.00	21.00	P3	53.18
SCE-24EL3008LP	24.00	30.00	8.00	E3	329.69	SCE-30P24	27.00	21.00	P3	63.29
SCE-24EL3010LP	24.00	30.00	10.00	E3	355.51	SCE-30P24	27.00	21.00	P3	63.29
SCE-30EL1606LP	30.00	16.00	6.00	E3	263.25	SCE-30P16	27.00	13.00	P3	45.57
SCE-30EL2008LP	30.00	20.00	8.00	E3	303.85	SCE-30P20	27.00	17.00	P3	55.70
SCE-30EL2010LP	30.00	20.00	10.00	E3	319.84	SCE-30P20	27.00	17.00	P3	55.70
SCE-30EL2408LP	30.00	24.00	8.00	E3	329.69	SCE-30P24	27.00	21.00	P3	63.29
SCE-30EL2410LP	30.00	24.00	10.00	E3	355.51	SCE-30P24	27.00	21.00	P3	63.29
SCE-30EL2412LP	30.00	24.00	12.00	E3	366.59	SCE-30P24	27.00	21.00	P3	63.29
SCE-30EL2416LP	30.00	24.00	16.00	E3	404.72	SCE-30P24	27.00	21.00	P3	63.29
SCE-30EL2420LP	30.00	24.00	20.00	E3	441.62	SCE-30P24	27.00	21.00	P3	63.29
SCE-30EL2424LP	30.00	24.00	24.00	E3	478.53	SCE-30P24	27.00	21.00	P3	63.29
SCE-30EL3008LP	30.00	30.00	8.00	E3	369.05	SCE-30P30	27.00	27.00	P3	83.55
SCE-30EL3010LP	30.00	30.00	10.00	E3	410.87	SCE-30P30	27.00	27.00	P3	83.55
SCE-30EL3012LP	30.00	30.00	12.00	E3	423.17	SCE-30P30	27.00	27.00	P3	83.55
SCE-30EL3608LP	30.00	36.00	8.00	E3	408.42	SCE-36P30	33.00	27.00	P3	101.27
SCE-36EL2408LP	36.00	24.00	8.00	E3	362.90	SCE-36P24	33.00	21.00	P3	75.96
SCE-36EL2410LP	36.00	24.00	10.00	E3	392.42	SCE-36P24	33.00	21.00	P3	75.96
SCE-36EL2412LP	36.00	24.00	12.00	E3	404.72	SCE-36P24	33.00	21.00	P3	75.96
SCE-36EL2416LP	36.00	24.00	16.00	E3	418.25	SCE-36P24	33.00	21.00	P3	75.96


Phone (989) 799-6871

Fax (989) 799-4524



**TYPE 4
ENVIROLINE® SERIES SINGLE-DOOR ENCLOSURES**

ENCLOSURES						SUB-PANEL				
Catalog No.	Height (A)	Width (B)	Depth (C)	Product Code	List Price	Catalog No.	Panel Height (D)	Panel Width (E)	Product Code	List Price
SCE-36EL3008LP	36.00	30.00	8.00	E3	408.42	SCE-36P30	33.00	27.00	P3	101.27
SCE-36EL3010LP	36.00	30.00	10.00	E3	435.47	SCE-36P30	33.00	27.00	P3	101.27
SCE-36EL3012LP	36.00	30.00	12.00	E3	452.70	SCE-36P30	33.00	27.00	P3	101.27
SCE-36EL3016LP	36.00	30.00	16.00	E3	498.22	SCE-36P30	33.00	27.00	P3	101.27
SCE-36EL3020LP	36.00	30.00	20.00	E3	542.51	SCE-36P30	33.00	27.00	P3	101.27
SCE-36EL3608LP	36.00	36.00	8.00	E3	452.70	SCE-36P36	33.00	33.00	P3	118.99
SCE-36EL3612LP	36.00	36.00	12.00	E3	501.91	SCE-36P36	33.00	33.00	P3	118.99
SCE-36EL3616LP	36.00	36.00	16.00	E3	551.11	SCE-36P36	33.00	33.00	P3	118.99
SCE-40EL2412LP	40.00	24.00	12.00	E3	428.10	SCE-40P24	37.00	21.00	P3	86.08
SCE-42EL2410LP	42.00	24.00	10.00	E3	457.63	SCE-42P24	39.00	21.00	P3	91.14
SCE-42EL3008LP	42.00	30.00	8.00	E3	449.01	SCE-42P30	39.00	27.00	P3	116.47
SCE-42EL3010LP	42.00	30.00	10.00	E3	471.15	SCE-42P30	39.00	27.00	P3	116.47
SCE-42EL3012LP	42.00	30.00	12.00	E3	496.98	SCE-42P30	39.00	27.00	P3	116.47
SCE-42EL3016LP	42.00	30.00	16.00	E3	528.98	SCE-42P30	39.00	27.00	P3	116.47
SCE-42EL3608LP	42.00	36.00	8.00	E3	499.46	SCE-42P36	39.00	33.00	P3	136.72
SCE-42EL3610LP	42.00	36.00	10.00	E3	524.06	SCE-42P36	39.00	33.00	P3	136.72
SCE-42EL3612LP	42.00	36.00	12.00	E3	551.11	SCE-42P36	39.00	33.00	P3	136.72
SCE-42EL3616LP	42.00	36.00	16.00	E3	605.24	SCE-42P36	39.00	33.00	P3	136.72
SCE-48EL2408LP	48.00	24.00	8.00	E3	429.32	SCE-48P24	45.00	21.00	P3	98.74
SCE-48EL2412LP	48.00	24.00	12.00	E3	477.30	SCE-48P24	45.00	21.00	P3	98.74
SCE-48EL3010LP	48.00	30.00	10.00	E3	512.98	SCE-48P30	45.00	27.00	P3	129.13
SCE-48EL3016LP	48.00	30.00	16.00	E3	574.49	SCE-48P30	45.00	27.00	P3	129.13
SCE-48EL3608LP	48.00	36.00	8.00	E3	542.51	SCE-48P36	45.00	33.00	P3	154.46
SCE-48EL3610LP	48.00	36.00	10.00	E3	573.27	SCE-48P36	45.00	33.00	P3	154.46
SCE-48EL3612LP	48.00	36.00	12.00	E3	600.33	SCE-48P36	45.00	33.00	P3	154.46
SCE-48EL3616LP	48.00	36.00	16.00	E3	658.14	SCE-48P36	45.00	33.00	P3	154.46
SCE-48EL3620LP	48.00	36.00	20.00	E3	715.97	SCE-48P36	45.00	33.00	P3	154.46
SCE-60EL2412LP	60.00	24.00	12.00	E3	551.11	SCE-60P24	57.00	21.00	P3	129.13
SCE-60EL3610LP	60.00	36.00	10.00	E3	667.98	SCE-60P36	57.00	33.00	P3	189.89
SCE-60EL3612LP	60.00	36.00	12.00	E3	698.74	SCE-60P36	57.00	33.00	P3	189.89
SCE-60EL3616LP	60.00	36.00	16.00	E3	765.17	SCE-60P36	57.00	33.00	P3	189.89
SCE-60EL3620LP	60.00	36.00	20.00	E3	832.83	SCE-60P36	57.00	33.00	P3	189.89
SCE-72EL3012LP	72.00	30.00	12.00	E3	749.18	SCE-72P30	69.00	27.00	P3	210.15
SCE-72EL3016LP	72.00	30.00	16.00	E3	856.21	SCE-72P30	69.00	27.00	P3	210.15
SCE-72EL3024LP	72.00	30.00	24.00	E3	941.08	SCE-72P30	69.00	27.00	P3	210.15
SCE-72EL3612LP	72.00	36.00	12.00	E3	799.62	SCE-72P36	69.00	33.00	P3	225.33
SCE-72EL3616LP	72.00	36.00	16.00	E3	910.33	SCE-72P36	69.00	33.00	P3	225.33



TYPE 4
Enviroline® Series
Single-Door Enclosures

Application -

Designed to house electrical and electronic controls, instruments and components. Provides protection from dust, oil and water. For outdoor application a drip shield is recommended.

Construction -

- 0.075" carbon steel.
- Seams continuously welded and ground smooth.
- Flange trough collar around all sides of door opening.
- Oil- resistant gasket.
- Collar studs provided for mounting optional panels.
- Concealed hinge.
- Removable and interchangeable doors.
- Black quarter turn latches.
- Latches are opened or closed with a screwdriver.
- Mounting holes in back of enclosure.
- Mounting hardware, sealing washer and hole plug included.
- Removable print pocket.
- Ground studs on door and body.

Options -

- Optional tamper-resistant inserts are available.
- Optional mounting feet available.
- Door hardware available.

Finish -

ANSI-61 gray powder coating inside and out. Optional panels are powder coated white.

Industry Standards -

NEMA Type 4, 12, & 13
UL Listed Type 4 & 12
CSA Type 4 & 12
IEC 60529 IP 66




Notes -

Interchangeable latches and handles available in the accessory section.



Phone (989) 799-6871
Fax (989) 799-4524

TYPE 4 ENVIROLINE® SERIES SINGLE-DOOR ENCLOSURES TECHNICAL DATA



SECTION A-A

SUB-PANEL NOTES:

Dimensions are from the inside of the door
 C + 0.32 [8.1] for flat sub-panels
 C - 0.18 [4.5] for bent sub-panels

LATCH NOTES:

Enclosures < 24.00" [609.6] in height require only one latch centered on door.
 Enclosures >= 24.00" [609.6] and < 40.00" [1016] in height require two latches on door.
 Enclosures >= 40.00" [1016] require three latches on door.
 Omit center latch top and bottom of door when door width is <= 30.00" [762]

ENVIROLINE® ENCLOSURES

- ✓ Enviroline® enclosures are an all purpose enclosure with a durable powder coat finish.
- ✓ Available in carbon steel and stainless.
- ✓ Available in disconnect styles, as well as free-standing enclosures.
- ✓ Enviroline® enclosures are NEMA 12/4 or NEMA 12/4/4X enclosures with quarter turn latches.
- ✓ Enviroline® enclosures feature the exclusive SCE removable hinge which allows the door to swing open 180°.
- ✓ The SCE designed hinge can be removed by removing the retaining clip and pulling the pin.
- ✓ The doors are interchangeable.
- ✓ Flange trough collar around door opening channels liquids away from the door.
- ✓ Easy to install swing out panel kits that mount to the concealed hinges.
- ✓ The quarter turn latches can be replaced with a variety of latches, including wing knob, keylocking, padlocking, coinproof, and tamper resistant inserts.
- ✓ Quarter turn latches can also be replaced with several handles, including chrome keylocking & padlocking, and the black 5" and 7" SCE handles, including keylocking, padlocking, and coinproof.
- ✓ A three-point latching system is available for enclosures over 40" high.
- ✓ Holes in back of the enclosure for mounting or installing optional mounting foot kit (SCE-ELMFK4). A hole plug kit is included if holes are not needed.